NSN 5305-00-297-8359

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-8359 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.688 inches **Fastener Length:** Between 0.734 inches and 0.736 inches **Head Diameter:** Between 0.280 inches and 0.290 inches **Head Height:** Between 0.165 inches and 0.185 inches **Extended Washer Diameter:** Between 0.360 inches and 0.380 inches **Extended Washer Thickness:** Between 0.043 inches and 0.053 inches First Diameter From Head: Between 0.155 inches and 0.165 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.078 inches and 0.109 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-297-8359

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0