Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-8449

| Thread Classe |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.219 inches |
| Fastener Length: |
| 0.348 inches |
| Head Style: |
| Round |
| Head Diameter: |
| Between 0.193 inches and 0.211 inches |
| Head Height: |
| Between 0.075 inches and 0.087 inches |
| Washer Quantity: |
| 1 |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 48 |
| Minimum Yield Strength: |
| 25000 pounds per square inch |
| Primary Washer Outside Diameter: |
| 0.250 inches |
| Primary Washer Style: |
| Split helical ring |
| Primary Washer Material Thickness: |
| 0.031 inches |
| Material: |
| Copper alloy 274 fastener |
| Material Specification: |
| Qq-w-321 federal specification single material response fastener |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| |

NSN 5305-00-297-8449

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

