## NSN 5305-00-298-2879



Shoulder Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-298-2879 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.265 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.420 inches and 0.460 inches **Head Height:** Between 0.110 inches and 0.150 inches **Shoulder Diameter:** 0.214 inches first shoulder and 0.217 inches first shoulder **Shoulder Length:** 0.141 inches first shoulder and 0.171 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A003b0