NSN 5305-00-298-3084



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-298-3084 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 0.910 inches and 0.940 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.303 inches **Shoulder Diameter:** 0.2016 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 0.503 inches first shoulder and 0.523 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-00-298-3084

Shoulder Screw - Page 2 of 2



Fiig:

A003b0