## NSN 5305-00-298-3368

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-298-3368 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.688 inches **Fastener Length:** 0.812 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.107 inches and 0.123 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.142 inches and 0.147 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Round internal hexagon **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 **Material Specification:** Ams 6370 assn standard single material response **Surface Treatment:** 

Cadmium

## NSN 5305-00-298-3368

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0