NSN 5305-00-298-8368

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-298-8368

view Online at https://aerobasegroup.com/nsn/5305-00-298-6368
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.434 inches and 0.442 inches
Fastener Length:
Between 0.594 inches and 0.597 inches
Head Style:
Dished hexagon
Head Height:
Between 0.302 inches and 0.324 inches
Width Between Flats:
Between 0.492 inches and 0.501 inches
Hole Diameter:
0.070 inches
Point Length:
Between 0.155 inches and 0.160 inches
Point Diameter:
Between 0.178 inches and 0.180 inches
Point Style:
Dog
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.250 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material
response or ams 6300 assn standard 6th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

NSN 5305-00-298-8368

Setscrew - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-s-5626 spec.