## NSN 5305-00-300-2213

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-300-2213 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.172 inches and 0.202 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.069 inches and 0.079 inches **First Diameter From Head:** Between 0.067 inches and 0.072 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.267 inches and 0.328 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-300-2213

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0