Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-300-2213

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.172 inches and 0.202 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Fillister
Head Diameter:
Between 0.166 inches and 0.183 inches
Head Height:
Between 0.069 inches and 0.079 inches
First Diameter From Head:
Between 0.067 inches and 0.072 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.267 inches and 0.328 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305
Material Specification:
Fed standard 66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-300-2213

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

