## NSN 5305-00-300-2219

Close Tolerance Screw - Page 1 of 2

3a

28





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.400 inches and 0.450 inches Fastener Length: Between 1.098 inches and 1.128 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.455 inches and 0.510 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Grip Length: Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or ams 6322 assn standard single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Shelf Life: Unit Of Measure: **Demilitarization:**

No

---

Unjf

N/a

## NSN 5305-00-300-2219

Close Tolerance Screw - Page 2 of 2

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

