## NSN 5305-00-302-9727



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-302-9727 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.312 inches **Fastener Length:** Between 0.282 inches and 0.312 inches **Head Style: Button Head Diameter:** Between 0.330 inches and 0.390 inches **Head Height:** Between 0.090 inches and 0.100 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Product Name:** Navy special project Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5305-00-302-9727

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0