NSN 5305-00-304-8715

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-304-8715 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.136 inches and 0.176 inches **Fastener Length:** Between 0.593 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.071 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.417 inches and 0.489 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1018 **Material Specification:** Qq-s-634 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-304-8715

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0