

View Online at <https://aerobasegroup.com/nsn/5305-00-305-1334>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

2.038 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.373 inches and 0.374 inches

**Head Height:**

0.560 inches

**Grip Diameter:**

Between 0.2481 inches and 0.2487 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Grip Length:**

1.613 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

15000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.900 inches first hole and 1.910 inches first hole

**Material:**

Steel comp 4340

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ps23041, fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0