NSN 5305-00-305-5474

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-305-5474 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.213 inches and 0.223 inches **Fastener Length:** Between 0.265 inches and 0.299 inches **Head Style:** Hexagon **Head Height:** Between 0.052 inches and 0.072 inches Width Between Flats: Between 0.183 inches and 0.193 inches **First Diameter From Head:** Between 0.061 inches and 0.064 inches **Second Diameter From Head:** Between 0.146 inches and 0.166 inches **Third Diameter From Head:** Between 0.057 inches and 0.067 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.025 inches and 0.029 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.030 inches and 0.044 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.052 inches and 0.076 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-305-5474

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0