NSN 5305-00-307-1473

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-307-1473 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 2.077 inches and 2.124 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.628 inches and 0.633 inches **Head Height:** Between 0.081 inches and 0.083 inches **Shoulder Diameter:** 0.327 inches first shoulder and 0.328 inches first shoulder **Shoulder Length:** 1.424 inches first shoulder and 1.446 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with o ring Material: Steel **Material Specification:** 3-53, fscm 76301 mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** 3-53 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-00-307-1473

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0