Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-307-1475

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.320 inches |
| Fastener Length: |
| Between 0.672 inches and 0.704 inches |
| Head Style: |
| Knurled no. 6 |
| Head Diameter: |
| 0.320 inches |
| Head Height: |
| Between 0.730 inches and 0.780 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.352 inches and 0.384 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 302 or steel comp 303 |
| Material Specification: |
| Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |