NSN 5305-00-307-1525

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-307-1525 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.168 inches and 0.208 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.198 inches and 0.270 inches **Internal Drive Style:** Cross recess type 1 **End Application:** 17n **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-307-1525

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0