NSN 5305-00-307-1547

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-307-1547 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 0.968 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.698 inches and 0.770 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-307-1547

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0