NSN 5305-00-307-1592

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-307-1592 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.595 inches and 0.625 inches **Fastener Length:** Between 3.100 inches and 3.120 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.729 inches and 0.750 inches **Head Height:** Between 0.302 inches and 0.312 inches **Shoulder Diameter:** 0.496 inches first shoulder and 0.498 inches first shoulder **Shoulder Length:** 2.495 inches first shoulder and 2.505 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-00-307-1592

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0