NSN 5305-00-308-1144

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-308-1144
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.053 inches and 0.125 inches
Fastener Length:
Between 0.095 inches and 0.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.154 inches and 0.161 inches
Head Height:
Between 0.095 inches and 0.099 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.099 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66
federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material
response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1352 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-00-308-1144

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0