## NSN 5305-00-308-1607

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-308-1607 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.102 inches and 0.183 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.207 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel **Head Surface Treatment:** Paint **Screw Surface Treatment: Passivate Bearing Surface Of Head Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Head Surface Treatment Specification:** Tt-e-527 federal specification single treatment response **Special Features:** Color no. 36231 federal standard 595 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-00-308-1607** Machine Screw - Page 2 of 2



Fiig:

A500d0