## NSN 5305-00-308-9469

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-308-9469 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.984 inches and 1.016 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-ans1351 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-308-9469

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0