

View Online at <https://aerobasegroup.com/nsn/5305-00-310-6018>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.431 inches

Fastener Length:

Between 0.829 inches and 0.859 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

High-torque

End Application:

Vengine, aircraft, f100-pw-100 (f-15a/b/c/d); aircraft, phantom f-4; aircraft, eagle f-15; support equipment, t-37 aircraft; support equipment, t-38 aircraft; aircraft, stratalifter c-135; aircraft, hornet f/a-18; aircraft, harrier av-8b

Thread Diameter:

0.190 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Stainless steel

Material Specification:

23-112, fscm 76301 mfr ref single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0