NSN 5305-00-310-6751

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-310-6751 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.208 inches and 0.258 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1218 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-310-6751Machine Screw - Page 2 of 2



Fiig:

A500d0