

View Online at <https://aerobasegroup.com/nsn/5305-00-310-8585>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.525 inches and 0.675 inches

**Fastener Length:**

Between 2.710 inches and 2.740 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.123 inches and 0.130 inches

**Hole Diameter:**

0.046 inches

**First Diameter From Head:**

0.140 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 2.065 inches and 2.185 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Round

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification 1st treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.