NSN 5305-00-310-8585

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-310-8585 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.525 inches and 0.675 inches **Fastener Length:** Between 2.710 inches and 2.740 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **Hole Diameter:** 0.046 inches First Diameter From Head: 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.065 inches and 2.185 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate**

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification 1st treatment response

NSN 5305-00-310-8585

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.