## NSN 5305-00-312-5799

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-312-5799

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.406 inches and 0.469 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style: Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Screw Material:
Steel comp 8630
Screw Material Specification:
Mil-s-6050 military specification single material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response
Head Hole Configuration Style:
Round
Special Features:
Groove in head 0.045 in. Min 0.065 in. Maximum w, 0.050 in. Min 0.070 in. Deep
Thread Series Designator:
Unc
Shelf Life:
N/a

## NSN 5305-00-312-5799

Machine Screw - Page 2 of 2



	~ .		
Init	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.