## NSN 5305-00-312-5799

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-312-5799

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.406 inches and 0.469 inches  |
| Fastener Length:   |
| Between 0.469 inches and 0.500 inches  |
|  |
| Head Style: Fillister  |
| Head Diameter:   |
|  |
| Between 0.250 inches and 0.270 inches  |
| Head Height:   |
| Between 0.106 inches and 0.113 inches  |
| Hole Diameter:   |
| 0.046 inches   |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.164 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 125000 pounds per square inch  |
| Screw Material:  |
| Steel comp 8630  |
| Screw Material Specification:  |
| Mil-s-6050 military specification single material response                     |
| Screw Surface Treatment:   |
| Cadmium  |
| Screw Surface Treatment Specification:   |
| Qq-p-416, type 1, cl 3 federal specification single treatment response         |
| Head Hole Configuration Style:   |
| Round  |
| Special Features:  |
| Groove in head 0.045 in. Min 0.065 in. Maximum w, 0.050 in. Min 0.070 in. Deep |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |

## NSN 5305-00-312-5799

Machine Screw - Page 2 of 2



|      | ~ .  |         |   |
|------|------|---------|---|
| Init | ( )t | Measure | • |
|      |      |         |   |

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.