## NSN 5305-00-312-8087



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-312-8087 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.844 inches **Head Style:** Flat chamfer **Head Diameter:** 0.437 inches **Head Height:** 0.187 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** Between 0.170 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.469 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** 0.035 to 0.040 in. Deep o-ring relief in. Head Material: Steel comp 1213 **Material Specification:** Qq-s-637 federal specification single material response **Surface Treatment:** Cadmium and chromate or enamel

Qq-p-416, type 2, cl 2 federal specification 1st treatment response or mil-e-15090 military specification 2nd treatment response

Unf

**Surface Treatment Specification:** 

**Thread Series Designator:** 

## NSN 5305-00-312-8087

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-e-15090 spec.