NSN 5305-00-315-3152

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-315-3152 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 1.813 inches **Head Style:** Knurled no. 1 **Head Diameter:** 1.500 inches **Head Height:** 0.437 inches Point Length: 0.125 inches First Diameter From Head: 1.000 inches **Second Diameter From Head:** Between 0.151 inches and 0.161 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.188 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.875 inches Point Style: Cone **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 60.0 degrees **Special Features:** Drilled and tapped hole no. 6-32 through head and shoulder Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response

Paint

Surface Treatment:

NSN 5305-00-315-3152

Thumbscrew - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Black pentrate 44286, fscm 24930 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0