## NSN 5305-00-316-0236



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-316-0236 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.185 inches and 0.215 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Pan **Head Diameter:** Between 0.146 inches and 0.176 inches **Head Height:** Between 0.034 inches and 0.064 inches **Shoulder Diameter:** 0.089 inches first shoulder and 0.099 inches first shoulder **Shoulder Length:** 0.660 inches first shoulder and 0.690 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 **Material Specification:** Mil-s-5626 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-316-0236

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.