NSN 5305-00-316-5907

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-316-5907 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.190 inches and 0.200 inches **Fastener Length:** Between 0.450 inches and 0.460 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.260 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-316-5907

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0