## NSN 5305-00-316-6848

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-316-6848 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.328 inches **Fastener Length:** Between 0.296 inches and 0.328 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **End Application:** Aircraft, b-2 bombe (atb); aircraft, tomcat f-14; aircraft, intruder a-6e; aircraft, eagle f-15; f/a-18 aircraft; ta-4j aircraft; harrier **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-316-6848

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0