

View Online at <https://aerobasegroup.com/nsn/5305-00-317-3102>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.156 inches

**Fastener Length:**

1.250 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.270 inches and 0.295 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

45.0 rockwell c primary washer and 53.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.635 inches and 0.651 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.094 inches

**Material:**

Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0