Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-318-8344

Thread Class: 2a 2b 2a 2b		
Thread Direction: Right-hand Thread Length: Between 0.170 inches and 0.190 inches Faster Length: Between 0.730 inches and 0.780 inches Head Style: Binding Head Director: Between 0.270 inches and 0.290 inches Head Height: Between 0.270 inches and 0.290 inches Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.020 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Interad Diameter: 0.138 inches Thread Diameter: 0.138 inches Thread Yer Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Q-sp-261 /2 hard federal specification single material response Surface Treatment: Q-sp-416, kype 1 of 3 federal specification single treatment response Surface Treatment: Q-sp-416, kype 1 of 3 federal specification single tr	Thread Class:	
Right-hand Firead Length: Between 0.170 inches and 0.190 inches Fastener Length: Between 0.730 inches and 0.780 inches Head Style: Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Diameter: Between 0.270 inches and 0.080 inches First Diameter From Head: Between 0.200 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.200 inches and 0.096 inches Internal Drive Style: Stor Pread Diameter: 0.130 inches and 0.610 inches Internal Drive Style: Stor Thread Diameter: 0.130 inches Thread Diameter: 0.138 inches Thread Store Material: Copper alloy 360 Material Que-for 1/2 hard federal specification single material response Surface Treatment: Cadmim Qu-p-416, type 1 of 3 federal specification single treatment response Thread Specification: Qu-p-416, type 1 of 3 federal specification singl	2a	
Tread Length: Between 0.170 inches and 0.190 inches Fastener Length: Between 0.730 inches and 0.780 inches Head Diameter: Between 0.270 inches and 0.290 inches Head Diameter: Between 0.070 inches and 0.080 inches Head Diameter: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.520 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Between 0.520 inches and 0.610 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Thread Diameter: 0.310 inches Thread Diameter: 0.320 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material: Cadmim Surface Treatment Specification single material response Cadmim Qu-p-416, type 1 d 3 federal specification single treatment response Thread Series Designator: Unc Shert Lie: <tr< th=""><th>Thread Direction:</th><th></th></tr<>	Thread Direction:	
Between 0.170 inches and 0.190 inches Fastener Length: Between 0.730 inches and 0.780 inches Head Style: Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.070 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thread Diameter: 0.138 inches Chread Yup Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material Copper alloy 360 Material Specification: Queb-261 J2 hard federal specification single material response Straface Treatment: Cadmium Queb-261 J2 hard federal specification single treatment response Thread Series Designator: Unc Shelf Life: Na Chrift Measure: Na<	Right-hand	
Pastenci Lengh: Between 0.730 inches and 0.780 inches Head Style: Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Height: Between 0.070 inches and 0.290 inches Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Oty Per Inch (tpl): 32 Externally Relieved Body Diameter Quantity: 1 Material Specification: Cay-be26 1/2 hard federal specification single material response Surface Treatment Cadmium Surface Treatment Specification Cay-be26 1/2 hard federal specification single treatment response Thread Series Designator: Vind Unc Sheff Life: Na Unit Of Measure: Image: I	Thread Length:	
Between 0.730 inches and 0.780 inches Head Style: Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Netween 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thready Oty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qu-p-456 1/2 hard federal specification single material response Surface Treatment Specification Qu-p-456 1/2 hard federal specification single treatment response Thread Series Designator: Qu-p-456, type 1 d 3 federal specification single treatment response Thread Series Designator: Na Via Thread Series Designator: Na Distance Treatment Specification Na Dire Series Designator:<	Between 0.170 inches and 0.190 inches	
Head Style: Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Oty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Q-p-626 1/2 hard federal specification single material response Surface Treatment Cadmium Surface Treatment Specification: Q-q-161, type 1 cl 3 federal specification single treatment response Thread Series Designator: Na Na Heriel Life: Na Exter Series Designator: Image: Dit Of Measure: Particitation:	Fastener Length:	
Binding Head Diameter: Between 0.270 inches and 0.290 inches Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Drive Style: Botween 0.520 inches and 0.610 inches Internal Style: Botween 0.520 inches and 0.610 inches Internal Specification: Boty Boty Boty Diameter Quantity: Boty Boty Boty Boty Boty Boty Boty Boty	Between 0.730 inches and 0.780 inches	
Head Diameter: Between 0.270 inches and 0.290 inches Head Heigh: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thread Viewer Def Viewer Dody Diameter Quantity: 1 Stot Material Copper alloy 360 Material Specification: Cap-be26 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Cap-be36 1/2 hard federal specification single treatment response Thread Specification: Cadmium Surface Treatment: Unc Shell Life: N/a Dit Of Measure: N/a Enternet: Dit Of Measure: - Enternet: Dit of Measure: -	Head Style:	
Between 0.270 inches and 0.290 inches Head Heigh: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material Copper alloy 360 Material Specification: Qu-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Garp-416, type 1 of 3 federal specification single treatment response Thread Specification: Qu-p-426, type 1 of 3 federal specification single treatment response Surface Treatment Qu-b-10, type 1 of 3 federal specification single treatment response Thread Sprise Designator: Unc Suff Life: N/a Dit Of Measure: Parameter Dit Of Measure: Parameter	Binding	
Head Height: Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment: Qarp-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: Na Unc Shelf Life: Na Unc Chesure: -	Head Diameter:	
Between 0.070 inches and 0.080 inches First Diameter From Head: Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qu-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification Qu-p-416, type 1 cl 3 federal specification single treatment response Thread Steries Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Ditt Of Measure: - Ditt Of Measure: - Demilitarization:	Between 0.270 inches and 0.290 inches	
First Diameter From Head: Between 0.000 inches and 0.006 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material Copper alloy 360 Material Specification: Qu-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Qu-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Sheff Life: Na Dird Measure: Ciff Comperation: Dird Measure:	Head Height:	
Between 0.090 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment: Cadmium Qq-p-416, type 1 of 3 federal specification single treatment response Thread Series Designator: Unc Sheff Life: N/a Unit Of Measure: - Demilitarization:	Between 0.070 inches and 0.080 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.520 inches and 0.610 inchesInternal Drive Style:SlotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloy 360Material Specification:Qu-b-626 1/2 hard federal specification single material responseSurface Treatment:CadmiumQu-p-416, type 1 of 3 federal specification single treatment responseThread Series Designator:UncSheff Life:NaCoper:UncSurface Treatment Specification single treatment responseThread Series Designator:UncSheff Life:NaDince:Dince:Comment:Dince:Dince:Comment:Dince:Dince:Dince:Comment:Dince:Comment:Dince:Comment: <t< td=""><td>First Diameter From Head:</td><td></td></t<>	First Diameter From Head:	
Between 0.520 inches and 0.610 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Sheft Life: N/a Unt Of Measure: - Emilitarization:	Between 0.090 inches and 0.096 inches	
Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Material Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Material Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit of Measure: Emilitarization:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
SlotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloy 360Material Specification:Qq-b-626 1/2 hard federal specification single material responseSurface Treatment:CadmiumQ-q-416, type 1 cl 3 federal specification single treatment responseThread Series Designator:UncSheft Life:N/aIncSheft Life:N/aDirder Measure:Camiter Comment:Dirder Comment: <tr< td=""><td>Between 0.520 inches and 0.610 inches</td><td></td></tr<>	Between 0.520 inches and 0.610 inches	
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization:	Internal Drive Style:	
0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Qq-b-626 1/2 hard federal specification single treatment response Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Inti Of Measure: 	Slot	
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Dint Of Measure: Demilitarization:	Thread Diameter:	
32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Gadmium Gurface Treatment Specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Litt Of Measure: 	0.138 inches	
Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Thready Qty Per Inch (tpi):	
1 Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - - Demilitarization:	32	
Material: Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Externally Relieved Body Diameter Quantity:	
Copper alloy 360 Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	1	
Material Specification: Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:	
Qq-b-626 1/2 hard federal specification single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Copper alloy 360	
Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Material Specification:	
Cadmium Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-b-626 1/2 hard federal specification single material response	
Surface Treatment Specification: Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment:	
Qq-p-416, type 1 cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Cadmium	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment Specification:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-p-416, type 1 cl 3 federal specification single treatment response	
Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization:	Unc	
Unit Of Measure: Demilitarization:	Shelf Life:	
 Demilitarization:	N/a	
	Unit Of Measure:	
No	Demilitarization:	
	No	

NSN 5305-00-318-8344

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

