NSN 5305-00-323-1951

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-323-1951



24 Firead Direction: Right-hand Thread Length: Between 1.376 inches and 1.500 inches Faster Length: Between 1.438 inches and 1.500 inches Head Signe: Round Head Dimeter: Between 0.287 inches and 0.309 inches Head Dimeter: 0.120 inches Head Dimeter: 0.120 inches Head Diameter: 0.120 inches Head Diameter: 0.120 inches Head Diameter: 0.120 inches Hered Diameter: 0.124 inches Thread Diameter: 0.124 inches Thread Diameter: 0.124 inches Thread Diameter: 0.124 inches Matrial: Nay special project Matrial: Stel comp 430 or stel comp 303 or stel comp 303se Stel Life: Nasivate Thread Steise Designator: Inc Matrial: Nation: Naion: Naion: <t< th=""><th>Thread Class:</th><th></th></t<>	Thread Class:	
Thread Direction: Right-hand Thread Length: Between 1.376 inches and 1.500 inches Fastener Length: Between 1.438 inches and 1.500 inches Head Style: Round Head Dimeter: Between 0.287 inches and 0.309 inches Head Dimeter: 0.120 inches Head Style: Oltzon inches Head Dimeter: 0.120 inches Head Style: Cross recess type 1 Thread Dimeter: 0.164 inches Thread Dimeter: 0.164 inches Thread Solience: Nay special project Material: Stel comp 430 or stel comp 303 or stel comp 303se Surface Treatment: Passivate Thread Solience: Nat Stel Life: Nat Chof Measure: Nat Dird Of Measure: - Penilitarization: Nat Stel Life: Nat Stel Life: <		
Right-hand Thread Length: Between 1.376 inches and 1.500 inches Fastener Length: Between 1.438 inches and 1.500 inches Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches O.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Diameter: 0.184 inches Thread Oinmeter: 0.184 inches Stelf Career Navy special project Material: Stelf Career Teatment: Passivate Thread Series Designator: Na Unit Of Measure: - Penilitarization: No Fig:		
Thread Length: Between 1.376 inches and 1.500 inches Fastener Length: Between 1.438 inches and 1.500 inches Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pollet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.176 inches Material: Store protect (tpi): 32 Product Name: Navy special project Material: Stel comp 430 or stel comp 303 or stel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: - Pomilitarization: No Fig:	Right-hand	
Fastener Length: Between 1.438 inches and 1.500 inches Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Y dy Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Steise Designator: Unc Shelf Life: Na Dint Of Measure: Tot Termal Direct Tot Parisona Direct Treatment: Na Direct Treatment: Na Direct Treatment: Product Name: Direct Treatment: Passivate Thread Series Designator: Na		
Between 1.43B inches and 1.500 inches Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Yal Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Steines Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pollet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Vaty Per Inch (tpi): 32 Product Name: Navy special project Material: Stel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Pasivate Thread Stel Stel Stel Stel Stel Stel Stel Stel	Fastener Length:	
Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Straface Treatment: Pasivate Thread Series Designator: Unc Shelf Life: Na Dird Measure: National Steel Comp Internation: Nation: Dird Measure: Internation: Nation: Steel Comp Internation: Nation: Steel Comp Internation: Nation: Steel Comp Internation: Nation: Steel Comp Internation: Natory Steel Comp Inter		
Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pollet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: N/a Dit of Measure: N/a Dit of Measure: Pro Thread Series Designator: N/a Dit of Measure: Pro Theol Series Designator: Pro Pro Dit of Measure: Pro Pro <td< th=""><th>Head Style:</th><th></th></td<>	Head Style:	
Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Intread Series Designator: Unc Shell Life: N/a Unt Of Measure: Penilitarization: No Fig:	Round	
Head Height:0.120 inchesLocking Feature:Pellet threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Steel comp 430 or steel comp 303 or steel comp 303seSurface Treatment:PassivateIntread Series Designator:UncShelf Life:NaDitt of Measure:rDemilitarization:NoFig:	Head Diameter:	
0.120 inches Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.287 inches and 0.309 inches	
Locking Feature: Pellet threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Penilitarization: No Fig:	Head Height:	
Pellet threads Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: 0.164 inches Thready Oty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	0.120 inches	
Internal Drive Style: Cross recess type 1 Cross recess type 1 Crhead Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Shelf Life: Na Dit Of Measure: Demilitarization: No	Locking Feature:	
Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Naterial: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Chit Of Measure: Demilitarization: No Fig:	Pellet threads	
Thread Diameter:0.164 inchesD.164 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Steel comp 430 or steel comp 303 or steel comp 303seSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnc for Measure:The Component of the Component o	Internal Drive Style:	
0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Passivate Unc Shelf Life: N/a Unc Dint Of Measure: Demilitarization: No Fig:	Cross recess type 1	
Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Diameter:	
32 Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.164 inches	
Product Name: Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Thready Qty Per Inch (tpi):	
Navy special project Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	32	
Material: Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Product Name:	
Steel comp 430 or steel comp 303 or steel comp 303se Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Navy special project	
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:	
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Steel comp 430 or steel comp 303 or steel comp 303se	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A003b0	Fiig:	
	A003b0	