NSN 5305-00-323-3465

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-323-3465 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.314 inches and 0.364 inches **Fastener Length:** Between 1.449 inches and 1.479 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r54520 **Material Specification:** Nas 621, 6al-4v assn standard single material response **Thread Series Designator:** Unjf 80205-nas633 professional/industrial association standard

Specification Data: Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-323-3465

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0