NSN 5305-00-324-8544

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-324-8544

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.443 inches and 0.510 inches |
| Fastener Length: |
| Between 1.078 inches and 1.125 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.501 inches and 0.506 inches |
| Head Height: |
| Between 0.071 inches and 0.073 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.615 inches and 0.635 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| 100.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Nas 621, 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A003b0 |
| |