## NSN 5305-00-324-9284

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-324-9284 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 3.329 inches and 3.359 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.2865 inches and 2.885 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 3.208 inches first hole and 3.248 inches first hole Material: Steel **Material Specification:** 23-112 fscm 76301 mfr ref single material response **Surface Treatment: Passivate Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-00-324-9284

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0