## NSN 5305-00-325-2461



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-325-2461 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.407 inches **Fastener Length:** Between 1.829 inches and 1.876 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-325-2461

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.