NSN 5305-00-328-9040



Mew Online at https://aerobasegroup.com/isn/5305-00-328-9040 Thread Class: 2a Thread Direction: Right-hand Thread Longth: 1.750 Inches Fasteor Length: 2.750 Inches Fasteor Length: 2.750 Inches Fasteor Length: 2.750 Inches Fasteor Length: 2.750 Inches Read Syle: Rund Head Dianeter: Between 0.287 Inches and 0.309 Inches Head Height: 0.120 Inches Internal Drive Style: Cross recess type 1 Thread Dianeter: 0.126 Inches Internal Drive Style: Cross recess type 1 Thread Dianeter: 0.136 Inches Internal Strength (psi): 6000 pounds per square inch Screw Material Specification: Oq=630 Inderal specification 2nd material response or qq=631 Inderal specification 2nd material response or qq=631 Inderal specification 2nd material response or qq=631 Inderal specification 2nd material response or qq=634 Inderal specification Oq=630 Inderal sp	Machine Screw - Page 1 of 1	
2a Fired Direction: Right and Thread Length: 1.750 Inches Pateman Length: 2.750 Inches Patema Length: 2.750 Inches Patema Length: 2.750 Inches Patema Length: 2.750 Inches Patema Dark Inches and 0.309 Inches Patema Dark Inches Patema Dark Inches Patema	View Online at https://aerobasegroup.com/nsn/5305-00-328-9040	
Fired Direction: Right-hand 1.750 inches Fastene Length: 2.750 inches Fastene Length: 2.750 inches Head Style: Round Head Dimeter: Between 0.297 inches and 0.309 inches Head Dimeter: 0.120 inches 10.120 inches Head Dimeter: 0.120 inches 10.120 inches Corss recess type 1 Corss recess type 1 Thread Diameter: 10.161 inches Thread Oly Per Inch (tpl): 22 Micro-Streag Diameter: 10.162 inches Screw Material Specification Rol Goup on dys per square inch Screw Material Specification 20 material response or qq-s-631 federal specification 2nd material response or qq-s-631 federal specificatin 2nd material response or qq-s-631 federal specificatin	Thread Class:	
Right-hand Tread Length: 1.750 inches Fastener Length: 2.750 inches Head Style: 7.750 inches Head Style: Round Head Diameter: Betwen 0.287 inches and 0.309 inches Head Height: 0.120 inches Internal Drive Style: Cross recess type 1 Otto Style: 0.164 inches Thread Diameter: 0.164 inches Thread Strength (psi): 80000 pounds per square inch 80000 pounds per square inch 9000 pounds per square inch	2a	
Fread-Length: 1.750 inches Pacher-Length: 2.750 inches Head Style: Round Head Style: Round Head Height: 0.120 inches Head Height: 0.120 inches Internal Drive Style: Cross recess type 1 Thread Drive Style: 0.164 inches Corss recess type 1 1.75 on Startength (psi): 8000 pounds per square inch Score Material Specification 2nd material response or qq-s-6.31 federal specification 2nd material response or qq-s-6.34 feder	Thread Direction:	
1750 incles Pastener Longth: 2750 incles Head Style: Round Head Dameter: Between 0.287 incles and 0.309 incles Head Neght: 0.120 incles Hortan Dive Style: 0.120 incles Mittener Dive Style: 17640 Dimeter: 0.120 incles Mittener Dive Style: 17640 Dimeter: 0.120 incles 17640 Dimeter: 0.200 pounds per square incle Stel or stel comp 1010 Stel or stel comp 1010 Stel or stel comp 1010 Ques-Stol federal specification 2nd material response or qq-S-631 federal specification 2nd material response Grap-Stol federal specification single treatment response Carbonic Icare Stries Designator: Icare Stries Designator: Icare Stries Designator: Icare Stries Designator:	Right-hand	
Fasteer Length: 2.750 inches Head Style: Round Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Interal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Intersol Strength (psi): 0.164 inches Porterol Diameter: 0.164 inches Porterol Diameter: 0.164 inches Porterol Diameter: 0.164 inches Second Caser style 1 10000 pounds per square inch 90000 pounds per square inch 9000	Thread Length:	
2.750 inches Action Act	1.750 inches	
Had Style: Round Had Diameter: Betwen 0.287 inches and 0.309 inches Head Height: 0.120 inches Had Joineter: 0.120 inches Toread Diameter: 0.141 inches Toread Diameter: 0.142 inches Toread Diameter: 0.143 inches Toread Diameter: 0.140 inches Toread Diameter: 0.401 inches Stread Vall Por Inch (pt): 32 Bottom Strength (psi): 60000 pounds per square inch Screw Material: Screw Material Specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-631 federal specification 2nd material response Screw Surface Treatment: Icadmiun Garce-Streatenter Specification insigle treatment response Icade Streat Specification insigle treatment response Icade Streat Specification insigle treatment response Icade Streat Specification Single treatment response Icade Streat Specification Insigle treatment response Icade Streat Specification Insigle treatment response </td <td>Fastener Length:</td> <td></td>	Fastener Length:	
Round Head Diameter: Betwen 0.287 inches and 0.309 inches. Hetwen 0.287 inches and 0.309 inches. Hetwen 0.287 inches and 0.309 inches. Hetwen 0.287 inches and 0.309 inches. Ditables: 10:20 inches Hetmathive Style: Cross recease type 1 Horead Diameter: 0:146 inches Thready Day Per Inch (tpl): 32 Min. Tonsile Strength (psi): 60000 pounds per square inch Score Material Specification: Qays-G30 federal specification 2nd material response or qq-s-631 federal specification 2nd material r	2.750 inches	
Head Diameter: Between 0.287 inches and 0.309 inches Head Height: 1.120 inches Incend Drive Style: Icross recess type 1 Thread Diameter: 0.164 inches Thready Oxy Per Inch (tpi): 32 Min. Tensile Strength (psi): 6000 pounds per square inch 0000 pounds per square inch Steel orapy 1010 Steel orapy 1010 9000 pounds per square inch	Head Style:	
Between 0.287 inches and 0.309 inches Head Height: 0.120 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Screw Material: Steel ors steel comp 1010 Screw Material Specification: 9 q-s-630 federal specification 2nd material response or qq-s-631 federal specif	Round	
Head Height: 1.120 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.148 inches Thread y Dry Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Screw Material: Screw Material: Screw Material Specification: Gadication 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal Specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal Screw Surface Treatment: Cadmim Area Series Designator: Interd Series Designator: <	Head Diameter:	
0.120 inches Internal Drive Style: Cross recess type 1 Cross recess type 1 Tread Diameter: C.164 inches Tready Qty Per Inch (tpl): C.164 inches Tready Qty Per Inch (tpl): C.164 inches C.165 Verse Varial Strength (psi): C.165 Verse Variatia: Steel or steel comp 1010 Steel vasteel comp 1010 C.164 inches C	Between 0.287 inches and 0.309 inches	
Interal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 0000 pounds per square inch 0000 pounds per square inch Stere Waterial: Stere Orns teel comp 1010 Stere Orns teel comp 1010 Stere Surface Treatment: Pace-Sol federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-	Head Height:	
Cross recess type 1 Thread Diamete: 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Screw Material: Steel or steel comp 1010 Grew Material Specification Qr.gr-s630 federal specification 2nd material response or qq-s-631 federal specification 2nd material 2nd qq-q-10, type 1, c	0.120 inches	
Thread Diameter 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Screw Material: Steel or steel comp 1010 Screw Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal Screw Surface Treatment: Cadmium Qq-p-416, type 1, cl 3 federal specification single treatment response Qrap-416, type 1, cl 3 federal specification single treatment response Intread Series Designator: Unc Shelf Life: Na Int of Measure: - - Penilitarization: Interface Treatment Specification single treatment response	Internal Drive Style:	
0.164 inchesTready Qty Per Inch (tpi):3234Min. Tensile Strength (psi):60000 pounds per square inchScrew Material:1Stel or steel comp 1010Screw Material Specification:Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federalSpecification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federalSpecification 2nd material responseGraw Surface Treatment:CadmiumQ-q-416, type 1, cl 3 federal specification single treatment responseTread Series Designator:IncShelf Life:NaInic Of Measure:iInic Of Measure:iNoFig:	Cross recess type 1	
Irready Qty Per Inch (tpi):32Min. Tensile Strength (psi):60000 pounds per square inchScrew Material:Steel comp 1010Screw Material Specification:Qq-s-630 federal specification 2nd material response or qq-s-631 federal specifi	Thread Diameter:	
32 Min. Tensile Strength (psi): 60000 pounds per square inch Screw Material: Stel or steel comp 1010 Screw Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response Grew Surface Treatment: Cadmium Garp-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Inc Na Ditle flife: Init of Measure: No Fig:	0.164 inches	
Min. Tensile Strength (psi):60000 pounds per square inchScrew Material:Steel or steel comp 1010Screw Material Specification:Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response Or qq-specification 2nd material response Or qq-specification 2nd material response	Thready Qty Per Inch (tpi):	
60000 pounds per square inch Screw Material: Steel or steel comp 1010 Grew Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response Grew Surface Treatment: Cadmium Aq-s-616, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: Na Int of Measure: - Demilitarization: Na Fig:	32	
Screw Material: Steel or steel comp 1010 Screw Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response specification 2nd material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification single treatment response Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unic of Measure: - Demilitarization: Na Director Fermine: Director Sing:	Min. Tensile Strength (psi):	
Steel or steel comp 1010 Screw Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-641 federal specification 2nd material	60000 pounds per square inch	
Screw Material Specification: Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response specification 2nd material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Screw Material:	
Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: - Demilitarization: No Fig:	Steel or steel comp 1010	
specification 2nd material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Fig:	Screw Material Specification:	
Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response o	r qq-s-634 federal
Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	specification 2nd material response	
Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Screw Surface Treatment:	
Qq-p-416, type 1, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cadmium	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Screw Surface Treatment Specification:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Qq-p-416, type 1, cl 3 federal specification single treatment response	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:		
Fiig:		
	No	
A500d0	Fiig:	
	A500d0	