NSN 5305-00-328-9086

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-328-9086

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| Between 2.656 inches and 2.750 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.292 inches and 0.313 inches |
| Head Height: |
| Between 0.123 inches and 0.130 inches |
| Hole Diameter: |
| 0.046 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 62000 pounds per square inch |
| Screw Material: |
| Aluminum alloy 2024 |
| Screw Material Specification: |
| Qq-a-225/6 federal specification single material response |
| Screw Surface Treatment: |
| Anodize |
| Screw Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unf |
| Specification Or Standard: |
| 1 type and 5s style |
| Shelf Life: |
| N/a |
| IN/a |

NSN 5305-00-328-9086

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.

