## NSN 5305-00-329-1987

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-329-1987 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.170 inches **Fastener Length:** Between 0.670 inches and 0.680 inches **Head Style:** Flat countersunk **Head Diameter:** 0.225 inches **First Diameter From Head:** Between 0.074 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.510 inches and 0.530 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Surface Treatment:** Oxide film **Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

## NSN 5305-00-329-1987

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.