Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-330-3748

## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.560 inches and 0.590 inches Fastener Length: Between 0.610 inches and 0.640 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Internal Drive Style:** Hexagon **End Application:** Medium mine protected vehicle - mmpv **Thread Diameter:** 0.112 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 80.0 rockwell b Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** 66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astma493 assn standard 6th material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a Unit Of Measure: ---

## NSN 5305-00-330-3748

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

