NSN 5305-00-331-4532

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-331-4532 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.328 inches **Fastener Length:** 1.604 inches **Head Style:** Flat chamfer **Head Diameter:** 0.372 inches **Head Height:** 0.156 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole First Diameter From Head: 0.247 inches **Second Diameter From Head:** 0.497 inches **Third Diameter From Head:** 0.422 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.156 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.229 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.276 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.479 inches first hole Material:

Thread Series Designator: Unf

Steel comp 4130

NSN 5305-00-331-4532

Externally Relieved Body Screw - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0