Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-331-4532

Thread	Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.328 inches

Fastener Length:

1.604 inches

Head Style:

Flat chamfer

Head Diameter:

0.372 inches

Head Height:

0.156 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

First Diameter From Head:

0.247 inches

Second Diameter From Head:

0.497 inches

Third Diameter From Head:

0.422 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.156 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.229 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.276 inches

Internal Drive Style:

Slot

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.479 inches first hole

Material:

Steel comp 4130

Thread Series Designator:

Unf

NSN 5305-00-331-4532

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0