Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-337-2798

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
1.750 inches
Head Style:
Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.133 inches and 0.156 inches
First Diameter From Head:
0.109 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
1.250 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
100000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Special Features:
Cone point
Color:
Olive drab head
Material:
Stainless steel
Material Specification:
Qq-s-763, type 300 series, cond b federal specification all material responses
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-std-171, finish 21.9 military specification single treatment response

Thread Series Designator:

Unc

NSN 5305-00-337-2798

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.