NSN 5305-00-338-1166

Setscrew - Page 1 of 2

Between 0.276 inches and 0.286 inches

Thread Direction:

Thread Length:

Fastener Length:

0.594 inches

Right-hand



View Online at https://aerobasegroup.com/nsn/5305-00-338-1166

| Н | ead Style: |
|----|---|
| F | lat chamfer |
| Н | lead Diameter: |
| В | etween 0.245 inches and 0.255 inches |
| Н | lead Height: |
| В | etween 0.183 inches and 0.193 inches |
| Н | ole Diameter: |
| 0 | .063 inches |
| Ρ | oint Length: |
| В | etween 0.307 inches and 0.317 inches |
| P | oint Diameter: |
| В | etween 0.0935 inches and 0.0950 inches |
| Ρ | oint Style: |
| В | all |
| lr | nternal Drive Style: |
| S | lot |
| Т | hread Diameter: |
| 0 | .190 inches |
| Н | ole Quantity: |
| 2 | |
| Н | ole Type: |
| D | rilled |
| N | onstandard Thread Pitch Diameter: |
| + | 0.1697/+0.1707 inches |
| Т | hready Qty Per Inch (tpi): |
| 3 | 2 |
| Н | ole Configuration Style: |
| R | ound longitudinal hole |
| V | laterial: |
| S | teel comp 1212 |
| V | laterial Specification: |
| S | ae assn standard single material response |
| S | urface Treatment: |
| С | admium |
| S | urface Treatment Specification: |
| | q-p-416 federal specification single treatment response |

NSN 5305-00-338-1166

Setscrew - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0