NSN 5305-00-338-1794

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-338-1794 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.445 inches and 0.495 inches **Fastener Length:** Between 0.705 inches and 0.735 inches **Head Style:** Pan **Head Diameter:** Between 0.597 inches and 0.612 inches **Head Height:** Between 0.203 inches and 0.218 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-338-1794

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0