NSN 5305-00-338-3257

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-338-3257

3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.401 inches and 0.451 inches	
Fastener Length:	
Between 1.036 inches and 1.066 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.464 inches and 0.506 inches	
Grip Diameter:	
Between 0.2490 inches and 0.2495 inches	
Internal Drive Style:	
High-torque	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.615 inches and 0.635 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Surface Finish:	
32.0 microinches threads	
Material:	
Titanium alloy	
Material Specification:	
Nas621 comp 6al-4v assn standard single material response or ams 4928 assn standard single	material response
Thread Series Designator:	
Unjf	
Specification Data:	
80205-nas664 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5305-00-338-3257

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

