## NSN 5305-00-338-3274

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-338-3274 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.401 inches and 0.451 inches **Fastener Length:** Between 1.286 inches and 1.316 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy **Material Specification:** Nas621 comp 6al-4v assn standard single material response or ams 4928 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas621 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-338-3274

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0